



KPF2K-20

Grease for the food industry GLS 380/N2 H1 Halal





ELKALUB GLS 380/N2 Grease food industry ELKALUB GLS 380/N2 is an aluminum complex soap grease based on paraffin oil. Due to the moderate base oil viscosity (72 mm²/s) and the NSF H1 registration, it can be used as a universal grease for plain and roller bearings as well as for gears in the food and pharmaceutical sectors. The aluminum complex soap thickener makes the fat sticky and waterproof. The corrosion protection is very good - conditional sea water resistance is given. Solid lubricants also improve the frictional resistance and the dry properties of the product. Experience shows that the miscibility of ELKALUB GLS 380/N2 with other aluminum soap greases is not a problem.

BASE OIL White oil Poly-alpha-olefin

THICKENER Aluminum complex solid lubricants

viscosity 72 mm²/s

OPERATING TEMPERATURE -25 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



• Guides & Curves

BUSINESS

- Food
- beverages
- Pharma & Medicine
- bearing manufacturer
- plant construction

FUNCTIONALITY

- Low-temperature grease
- Food grease

PACKING

- 250 g tube
- 400 g cartridge
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo-Fr 09-16 Uhr