

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



KP2K-20

Grease for the food industry GLS 382/N2 H1 Halal



The lubricating grease ELKALUB GLS 382/N2 has been designed for application in roller and slide bearings as well as slipways and open lubricating points.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL White oil Other

THICKENER Aluminum complex solid lubricants

VISCOSITY 220 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 2

FIELD OF USE

- Guides & Curves

FUNCTIONALITY

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- lubricant
-

PACKING

- 250 g tube
 - 400 g cartridge
 - 1 kg can
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com