



KPHC1N-30

grease for linear guides VP 922 H1 Halal



ELKALUB VP 922 is a fully synthetic high-performance grease for the lubrication of rolling and sliding processes. The product is particularly suitable for the lubrication of highly loaded drive elements based on ball gears or screw drives. The high base oil viscosity in connection with solid lubricants and additives to improve sliding friction has a vibration and noise dampening effect and thus ensures a smooth and smooth operation of the drive. The solid lubricants also ensure emergency running properties in the limit friction area and in the event of a lack of lubricant. Thanks to the NSF H1 registration, ELKALUB VP 922 can be used in the food industry or other hygiene-sensitive areas.

BASE OIL Poly-alpha-olefin Other

THICKENER polyurea solid lubricants

VISCOSITY 320 mm²/s

OPERATING TEMPERATURE -30 °C bis 140 °C

NLGI CLASS 1

FIELD OF USE

- roller bearing
 - Linear guides & ball screws
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BUSINESS

- Food
- beverages
- Pharma & Medicine
- drive technology
- bearing manufacturer

FUNCTIONALITY

- Food grease

PACKING

- 250 g tube
 - 1 kg can
 - 5 kg bucket
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com