



Grease spray FLC 367 H1 Halal



ELKALUB FLC 367 is a partly synthetic EP-grease spray with high adhesive strength for the lubrication of chains, slideways, disk cams, gear racks etc. under an increased influence of water, vapour, acids and alkalis (in the pH-range 2-11 up to 50 °C). Even after cleaning procedures there remains a very thin lubricating film which at the same time protects against corrosion. ELKALUB FLC 367 penetrates well into joints and gaps. The product is suitable for application in the temperature range from -20 °C up to +130 °C (short time +180 °C). ELKALUB FLC 367 is NSF H1-approved and is therefore suited for environments with incidental food contact. Registration no. (H1): 126161

BASE OIL White oil

OPERATING TEMPERATURE -20 °C bis 130 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 165 mm²/s

FIELD OF USE

- bearings
- open gears
- racks
- Guides & Curves

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- print
- Food
- beverages
- Pharma & Medicine
- drive technology
- Furniture
- plant construction

FUNCTIONALITY

- Food grease
- lubricant
- corrosion protection
- universal

PACKING

- 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com