



KP000K-10

Grease for the food industry GLS 367/N000 H1 Halal



ELKALUB GLS 367/N000 is a partly synthetic lubricating grease for application in the food industry. The product is extremely adhesive and is especially suitable for gears subject to deficient lubrication due to a spin-off of the lubricant. The product can also be applied for slowturning antifriction bearings, for slip motions and for the lubrication of chains, valves, spindles, sterilizers etc. ELKALUB GLS 367/N00 is resistant to water, acids and alkalis. ELKALUB GLS 367/N00 is suitable for temperatures from -10 °C up to +130 °C (short-time up to 180 °C).

BASE OIL White oil Other

THICKENER Inorganic

VISCOSITY 200 mm²/s

OPERATING TEMPERATURE -10 °C bis 130 °C

NLGI CLASS 000

FIELD OF USE

- transmission
- chain

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Food
- beverages
- Pharma & Medicine

FUNCTIONALITY

- Food grease
- fluid grease

PACKING

- 1 kg can
 - 2 kg bag
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com