



KP1H-20

## Gear grease for power tools VP 820

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

**BASE OIL** mineral oil

---

**THICKENER** sodium

---

**VISCOSITY** 220 mm<sup>2</sup>/s

---

**OPERATING TEMPERATURE** -20 °C bis 100 °C

---

**NLGI CLASS** 1

---

**FIELD OF USE**

- transmission
- 

**BUSINESS**

- Power Tools
- 

**FUNCTIONALITY**

- fluid grease
- 

**PACKING**

- 250 g tube
- 400 g cartridge

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

# ELKALUB



*Hochleistungs-Schmierstoffe*  
*High Performance Lubricants*

- 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)