



# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**

KPHC1N-40

## Sliding grease GLS 993

ELKALUB GLS 993/N1 is an EP-gelgrease for the lubrication of gears and bearings at low speed, mostly for sliding movements, e.g. fittings, slide bars, regulators, as stopcock grease, tablet presses (upper dies), bottling machines etc. ELKALUB GLS 993/N1 can also be used as silicone-free form parting compound.

**BASE OIL** Poly-alpha-olefin

**THICKENER** Inorganic solid lubricants

**VISCOSITY** 400 mm<sup>2</sup>/s

**OPERATING TEMPERATURE** -40 °C bis 150 °C

**NLGI CLASS** 1-2

### FIELD OF USE

- bearings
- Fittings & O-rings
- Pneumatics
- valves
- fittings

### BUSINESS

- drive technology
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

## FUNCTIONALITY

- assembly grease
  - Low-temperature grease
- 

## PACKING

- 250 g tube
  - 400 g cartridge
  - 5 kg bucket
  - 18 kg hobbock
  - 50 kg hobbock
  - 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)