



# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**

KPF2G-10

## Adhesive grease for the food industry GLS 388/N2 H1 Halal



ELKALUB GLS 388/N2 is an extremely adhesive aluminium complex soap grease based on partly synthetic base oils with a high resistance to water (also salt water). ELKALUB GLS 388/N2 is suitable for temperatures from -10 °C up to +100 °C. The main areas of application are slow-turning drive elements such as joints, shafts, open cogwheels, sliding motions in the food industry. ELKALUB GLS 388/N2 is most suitable for pairings of nonferrous metals and steel.

**BASE OIL** White oil Poly-alpha-olefin Other

---

**THICKENER** Aluminum complex solid lubricants Others

---

**VISCOSITY** 72 mm<sup>2</sup>/s

---

**OPERATING TEMPERATURE** -10 °C bis 100 °C

---

**NLGI CLASS** 2

---

**FIELD OF USE**

- open gears
  - racks
  - Guides & Curves
- 

**BUSINESS**

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Food
- beverages
- Pharma & Medicine
- plant construction

---

#### FUNCTIONALITY

- Food grease
- lubricant

---

#### PACKING

- 250 g tube
  - 400 g cartridge
  - 5 kg bucket
  - 18 kg hobbock
  - 50 kg hobbock
  - 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)