



KPFHC2N-20

high-load grease VP 873 H1 Halal





ELKALUB VP 873 is a grease for heavily loaded roller bearings (especially tapered and spherical roller bearings, cam rollers)

Due to the high load-bearing capacity and the high wear protection, **ELKALUB VP 873** is also used as a lubricant in open gears. The lubrication points benefit from the adhesive formulation, which is also responsible for a high level of corrosion protection and water resistance.

The addition of solid lubricants supports sliding pairings and ensures emergency running properties.

ELKALUB VP 873 is suitable for metal-plastic combinations. Due to the diversity of plastic materials, a previous resistance test is recommended.

A special application of **ELKALUB VP 873** is as an assembly paste for stainless steel screw connections in the food industry. The grease prevents cold welding.

BASE OIL White oil Other

THICKENER polyurea solid lubricants

viscosity 460 mm²/s

OPERATING TEMPERATURE -20 °C bis 140 °C

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr



NLGI CLASS 1 - 2

FIELD OF USE

- roller bearing
- bearings
- open gears
- racks
- · Guides & Curves

BUSINESS

- Food
- beverages
- Pharma & Medicine
- drive technology
- bearing manufacturer

FUNCTIONALITY

- assembly grease
- High temperature grease
- Food grease
- Against tribocorrosion
- lubricant

PACKING

- 250 g tube
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo - Fr 09 - 16 Uhr