

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



High-temperature grease spray FLC 95

ELKALUB FLC 95 is an entirely synthetic, creepable grease spray with excellent adhesion and EP properties. It is free from silicones. ELKALUB FLC 95 is used for longer intervals of relubrication for temperatures up to 150 °C. However, it can also be used up to 220 °C if there is frequent relubrication. Examples of use for ELKALUB FLC 95 are chains (e.g. shrink tunnels, drying tunnels), joints and spindles in the high temperature and hot air range. The spray is bottled free from FCKW.

BASE OIL Poly-alpha-olefin

THICKENER polyurea

OPERATING TEMPERATURE -30 °C bis 170 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 400 mm²/s

FIELD OF USE

- bearings
- chain
- open gears
- racks
- Guides & Curves

BUSINESS

- drive technology
- Furniture
- Wood

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- plant construction
-

FUNCTIONALITY

- High temperature grease
 - noise
 - lubricant
 - corrosion protection
-

PACKING

- 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com