



High-temperature oil spray FLC 4010 H1 Halal



ELKALUB FLC 4010 is used for the lubrication of chains, joints, rollers, slideways, spindles, gripper seats in the UV- and varnish range for temperatures from -35 °C till +180 °C (+200 °C with constant relubrication). The high creeping ability of ELKALUB FLC 4010 guarantees that the lubricating film is also formed on the inner friction surfaces endangered by wear. After evaporation of the solvent, there remains a transparent, very adhesive film of high compressive strength. ELKALUB FLC 4010 is available as an aerosol and also in liquid form.

BASE OIL ester

THICKENER polyurea

OPERATING TEMPERATURE -35 °C bis 180 °C

VISCOSITY AT 40 °C (ACTIVE SUBSTANCE) 160 mm²/s

FIELD OF USE

- bearings
- Guides & Curves

BUSINESS

- print
- Food

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- beverages
- Pharma & Medicine
- drive technology
- Furniture
- plant construction

FUNCTIONALITY

- High temperature grease
- Low-temperature grease
- Food grease
- lubricant

PACKING

- 5 l canister
 - 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com