



High-temperature oil spray FLC 4010 P H1 Halal



FLC 4010 P is used for the lubrication of chains, joints, rollers, guides, spindles in the temperature range from -35 °C till +180 °C (with continuous relubrication up to +200 °C). The high creep ability ensures that internal friction surfaces prone to wear are lubricated. After the solvent has evaporated, a transparent, very pressure and adhesive film remains. In offset printing machines, ELKALUB FLC 4010 P is suitable for the lubrication of gripper seats (especially under UV light conditions and in the coating area). ELKALUB FLC 4010 P is supplied in 300 ml pump spray cans.

BASE OIL ester

THICKENER polyurea

OPERATING TEMPERATURE -35 °C bis 180 °C

VISCOSITY AT 40 °C (ACTIVE SUBSTANCE) 160 mm²/s

FIELD OF USE

- bearings
 - Guides & Curves
-

BUSINESS

- print
- Food

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- beverages
- Pharma & Medicine
- drive technology
- Furniture
- plant construction

FUNCTIONALITY

- High temperature grease
- Low-temperature grease
- Food grease
- lubricant

PACKING

- 300 ml pump spray
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com