



KP2K-20

High-load grease GLS 131/N2

ELKALUB GLS 131/N2 is a universal grease with high pressure absorption and very good adhesion. The grease can be used in roller and plain bearings as well as in open lubrication points. The speed characteristic in ball bearings is 250,000 mm / min-1.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL mineral oil

THICKENER lithium

VISCOSITY 320 mm²/s

OPERATING TEMPERATURE -20 °C bis 130 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- Guides & Curves

BUSINESS

- drive technology
- bearing manufacturer

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- plant construction
- miscellaneous

FUNCTIONALITY

- lubricant
- universal

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com