



Chain and adhesive lubricant FLC 8 H1 H1 Halal



ELKALUB FLC 8 H1 is our chain lubricant ELKALUB FLC 8 H1 in spray form. ELKALUB FLC 8 H1 is a further development of our chain lubricant ELKALUB LA 8. The lubricating film has a good spreading capability and protects against corrosion. It has excellent boundary lubrication properties and is very adhesive and resistant to centrifugation up to 80 °C. ELKALUB FLC 8 H1 is recommended for use in heavy drive chains, cams, disk cams, open cogwheels, slideways and spindles.

BASE OIL ester Other

THICKENER polyurea

OPERATING TEMPERATURE -20 °C bis 120 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 6000 mm²/s

FIELD OF USE

- chain
 - open gears
 - racks
 - Guides & Curves
 - fittings
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

BUSINESS

- print
 - Food
 - beverages
 - Pharma & Medicine
 - drive technology
 - Furniture
 - Wood
 - plant construction
-

FUNCTIONALITY

- Food grease
 - noise
 - lubricant
 - corrosion protection
-

PACKING

- 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com