



Chain and sliding spray FLC 1010/1012 P

ELKALUB FLC 1010/1012 P is an oil spray without any solid lubricants based upon our EP lubricating concentrate ELKALUB LA 1. It is resistant to aging, chemically neutral, dirt dissolving, protects against corrosion, does not become resinous and displaces water from surfaces. After spraying on the parts to be lubricated, there remains only a very thin, transparent and adhesive film. The extremely creeping special lubricant guarantees, that the lubricating film is also forming in very narrow fits where it lubricates reliably. Slightly rusty or coked parts become mobile again and the loosening is supported. Although ELKALUB FLC 1010/1012 P creeps well into fits, the creeping ability on surfaces is minimal. This is of advantage e.g. for grippers and transport chains. ELKALUB FLC 1010/1012 P is available as a pump spray bottle (300 ml)

BASE OIL ester mineral oil

OPERATING TEMPERATURE -20 °C bis 120 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 60 mm²/s

FIELD OF USE

- bearings
- chain
- Guides & Curves

BUSINESS

- print
- drive technology
- Furniture
- Wood

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- plant construction
-

FUNCTIONALITY

- corrosion protection
 - universal
-

PACKING

- 300 ml pump spray
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com