



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

Chain and adhesive lubricant LA 8

ELKALUB LA 8 is a highly viscous special lubricant which at the same time possesses an excellent creeping ability. ELKALUB LA 8 is mainly intended for the lubrication of highly loaded chain transmissions. The very adhesive film with EP and boundary lubrication capabilities, which is formed by ELKALUB LA 8 is extremely resistant against centrifugal forces and pressure. ELKALUB LA 8 is recommended or prescribed by leading printing press manufacturers. ELKALUB LA 8 is used straight for all types of chain transmissions or as an additive (5-20 %) for mineral oils for all points of lubrication which need a particularly adhesive type of lubricant. ELKALUB LA 8 has an anti-noise effect. Examples for application: Delivery chains, guide rails, eccentrics, gripper opening curves, open gear wheels, chain guideways.

BASE OIL ester mineral oil

THICKENER polyurea

OPERATING TEMPERATURE -5 °C bis 80 °C

VISCOSITY AT 40 °C 6000 mm²/s

FIELD OF USE

- transmission
 - chain
-

BUSINESS

- print
 - drive technology
 - plant construction
-

FUNCTIONALITY

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- lubricant
-

PACKING

- 1 liter can
 - 5 l jug
 - 20 l jug
 - 200 l barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com