



oil spray FLC 3010 H1 Halal



ELKALUB FLC 3010 is a partly synthetic oil spray which creeps extremely well into fits and joints where it lubricates reliably. The film protecting against corrosion offers a good protection against wear. ELKALUB FLC 3010 is recommended for a temperature range from -20 °C up to +120 °C. ELKALUB FLC 3010 possesses the H1-approval under NSF Registration no. (H1) 126162. Examples for application: Foil transport chains, transmission chains, joints, hinges, bearings, slideways. Note: For areas where there is a larger impact of water, vapour, acids and alkalis (pH-range 2-11 at 50 °C) we recommend our grease spray with H1 approval ELKALUB FLC 367.

BASE OIL White oil

OPERATING TEMPERATURE -20 °C bis 120 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 68 mm²/s

FIELD OF USE

- bearings
- chain
- Pneumatics
- valves
- Guides & Curves

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Food
- beverages
- Pharma & Medicine
- drive technology
- plant construction

FUNCTIONALITY

- Food grease
- corrosion protection
- universal

PACKING

- 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com