



Solvent and cleaner for PFPE lubricants LFC 500

ELKALUB LFC 500 is a solvent and cleaner for polyfluoropolyether-based (PFPE) lubricants. The product is used to pre-clean components which are subsequently lubricated with PFPE lubricant. Pre-cleaning improves the PFPE lubricants' perfect adhesion and is therefore recommended before initial application or re-lubrication. Due to ELKALUB LFC 500's high levels of solvency and capability, the product is ideally suited for removing used PFPE greases. The product is volatile. A quick processing and the corresponding preparation is recommended for economic and effective use.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL PFPE

OPERATING TEMPERATURE -40 °C bis 50 °C

BUSINESS

- Automotive
 - Power Tools
 - drive technology
 - Furniture
 - Wood
 - bearing manufacturer
 - plant construction
-

FUNCTIONALITY

- Rinse oil / cleaning oil
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

PACKING

- 1 liter can
 - 5 l jug
 - 50 ml bottle
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com