



GPPG00K-30

Polyglycol fluid grease GLG 886/N00 H1 Halal



ELKALUB GLG 886 / N00 is a fluid grease for gear lubrication. The polyglycol grease has very good coefficients of friction and is therefore particularly suitable for gearboxes with high sliding components (worm and hypoid gearboxes, screw jacks) ELKALUB GLG 886 / N00 has NSF H1 certification and can therefore be used in food processing areas. A typical area of application is small gear units on filling systems and packaging machines. Please note: ELKALUB GLG 886 / N00 cannot be mixed with conventional mineral oil-based greases. Before use, the compatibility with plastics, elastomers (except EPDM) and coatings (e.g. interior paints) must be checked.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL polyglycol

THICKENER Inorganic

VISCOSITY 180 mm²/s

OPERATING TEMPERATURE -30 °C bis 120 °C

NLGI CLASS 00

FIELD OF USE

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr****ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH**Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- transmission

BUSINESS

- print
- Food
- beverages
- Pharma & Medicine
- drive technology
- plant construction

FUNCTIONALITY

- Food grease

PACKING

- 2 kg bag
 - 18 kg hobbock
 - 50 kg hobbock
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com