

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants



KPSI3R-40

silicone grease GLS 794/N3 H1 Halal



ELKALUB GLS 794/N3 is a fully synthetic special grease for application in food, beverage and pharmaceutical industries. It is particularly suited for slide pairings (e.g. taps, valves, fittings) and as a mounting grease. The product is very resistant against water and steam and can be used for operating temperatures from -40 °C up to +180 °C. As a special feature for beverage dispensers and breweries: ELKALUB GLS 794/N3 does not have any influence on the formation of beer foam (see report of TU Munich, 15.06.2016).

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL silicone

THICKENER solid lubricants

VISCOSITY 1000 mm²/s

OPERATING TEMPERATURE -40 °C bis 180 °C

NLGI CLASS 3

FIELD OF USE

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Fittings & O-rings
- valves

BUSINESS

- Food
- beverages
- Pharma & Medicine

FUNCTIONALITY

- assembly grease
- High temperature grease
- Low-temperature grease
- Food grease

PACKING

- 200 ml brush box
 - 250 g tube
 - 380 g LubeShuttle
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com