



## Silicone special grease GLS 42

**ELKALUB GLS 42** is a smooth special silicone grease for all types of sliding processes.

Due to the solvent content, the grease can be sprayed easily. After the subsequent evaporation of the solvent, a highly adhesive and highly viscous lubricating film remains.

If required, the solvent content can be varied and adapted to the specific spray application.

**ELKALUB GLS 42** can be used in a wide temperature range (-30 °C /+180 °C); for use at higher temperatures, wait for the solvent to evaporate (typically: 12-36 hours/room temperature).

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

**BASE OIL** silicone

**THICKENER** solid lubricants

**VISCOSITY** 370 mm<sup>2</sup>/s

**OPERATING TEMPERATURE** -30 °C bis 180 °C

**NLGI CLASS** 1

**FIELD OF USE**

- bearings
- Fittings & O-rings
- valves
- Guides & Curves

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

## BUSINESS

- Furniture
  - plant construction
  - miscellaneous
- 

## FUNCTIONALITY

- Low-temperature grease
  - Lubricant / release agent
- 

## PACKING

- 1 kg can
  - 5 kg bucket
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)