



Silicone Spray FLC 700

Highly viscous glidant (approx. 22500 mm²/s at 40°C) which at the same time conserves the surface and protects against corrosion. After evaporation there remains a non-sticky film of long endurance. The transparent lubricating film is dirt repelling and does not leave any spots. Application for paper, cardboard, wood, rubber, plastics and fibre materials. Spray filling with: light hydrocarbons, butane.

BASE OIL silicone

OPERATING TEMPERATURE -50 °C bis 170 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 22500 mm²/s

FIELD OF USE

- Fittings & O-rings
- Guides & Curves

BUSINESS

- print
- drive technology
- Furniture
- bearing manufacturer
- plant construction

FUNCTIONALITY

- Lubricant / release agent
- corrosion protection

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

PACKING

- 5 l canister
 - 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com