



## silicone Spray FLC 745 H1 Halal



ELKALUB FLC 745 is a medium-viscous glidant (approx. 260 mm<sup>2</sup>/s at 40 °C) USDA H1 approved (Registration No. 126160) The transparent, non-smelling lubricating film protects and conserves the surface. The product is mainly used in food industries or in printing plants for food packaging. It is suited for foils and plastics (e.g. conveyors) as well as for rubber (e.g. rollers), paper and on metal surfaces. Spray filling with: light hydrocarbons, butane. Registration no. (H1): 126160

**BASE OIL** silicone

**OPERATING TEMPERATURE** -50 °C bis 170 °C

**VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE)** 260 mm<sup>2</sup>/s

#### FIELD OF USE

- Fittings & O-rings
- Guides & Curves

#### BUSINESS

- print
- Food
- drive technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Furniture
- bearing manufacturer
- plant construction

---

#### FUNCTIONALITY

- Food grease
- Lubricant / release agent
- corrosion protection

---

#### PACKING

- 400 ml of aerosol
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)