



KPF1K-25

## Special grease against Tribocorrosion GLS 361/N1 H1 Halal



**ELKALUB GLS 361/N1** is a special grease to avoid tribocorrosion. It combines a high load capacity with excellent wear protection against fretting corrosion caused by vibrations/oscillations. **ELKALUB GLS 361/N1** can be used best in open gear drives, shaft to collar connections and all other applications with high frictional wear. A special use of **ELKALUB GLS 361/N1** is the lubrication of drive cams of the perfecting drum in offset printing machines.

[Fit to go back and forth](#)

BASE OIL White oil Other

THICKENER polyurea solid lubricants

VISCOSITY 100 mm<sup>2</sup>/s

OPERATING TEMPERATURE -25 °C bis 1200 °C

NLGI CLASS 1

FIELD OF USE

- open gears
- racks

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)

## BUSINESS

- print
- Food
- beverages
- Pharma & Medicine

---

## FUNCTIONALITY

- assembly grease
- Food grease
- Against tribocorrosion

---

## PACKING

- 200 ml brush box
  - 100 g cartridge
  - 400 g cartridge
  - 1 kg can
  - 5 kg bucket
  - 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)