



# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**

KP2K-20

## Special grease GLS 135/N2

ELKALUB GLS 135/N2 is a lithium-saponified, water resistant and corrosion inhibiting universal grease. It can be used for roller and slide bearings in the temperature range from -20 °C to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of linear guidance systems as well as for ball bearings up to a speed factor ndm of 500.000. ELKALUB GLS 135/N2 has a very low oil bleeding and separation tendency. Therefore it is well conveyable in central lubricating systems (conveying test at bielomatik and Lincoln).

**BASE OIL** ester mineral oil

**THICKENER** Lithium special

**VISCOSITY** 100 mm<sup>2</sup>/s

**OPERATING TEMPERATURE** -20 °C bis 120 °C

**NLGI CLASS** 2

### FIELD OF USE

- roller bearing
- bearings
- Linear guides & ball screws
- Guides & Curves

### BUSINESS

- print
- drive technology

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Wood
- bearing manufacturer
- plant construction

---

#### FUNCTIONALITY

- noise

---

#### PACKING

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

---

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)