



KPIK-20

Spezial grease GLS 135/N1

ELKALUB GLS 135/N1 is a lithium-saponified, water resistant universal grease of high efficiency. ELKALUB GLS 135/N1 protects against corrosion and can be used for roller and slide bearings in the temperature range from -20 °C up to +120 °C. The short-fibred and homogeneous grease is excellently suitable for the lubrication of ball bearings up to a speed factor ndm of 500.000. as well as for linear units. ELKALUB GLS 135/N1 is well conveyable in central lubricating systems.

BASE OIL ester mineral oil

THICKENER Lithium special

VISCOSITY 100 mm²/s

OPERATING TEMPERATURE -20 °C bis 120 °C

NLGI CLASS 1

FIELD OF USE

- roller bearing
 - bearings
 - Linear guides & ball screws
 - Guides & Curves
-

BUSINESS

- print
 - drive technology
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Wood
- bearing manufacturer
- plant construction

FUNCTIONALITY

- noise

PACKING

- 250 g tube
- 100 g cartridge
- 380 g LubeShuttle
- 400 g cartridge
- 1 kg can
- 5 kg bucket
- 18 kg hobbock
- 50 kg hobbock
- 150 kg barrel

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com