

**KP00K-20**

Special fluid grease GLS 135/N00

ELKALUB GLS 135/N00 is a lithium-saponified semi-liquid grease with high performance. It has been designed for use in roller and slide bearings in the temperature range from -20 °C up to +120 °C. This short-fibred and homogenous grease is excellently suitable for the lubrication of ball bearings with a speed index of up to 500.000 as well as for linear units.

BASE OIL ester mineral oil**THICKENER** Lithium special**VISCOSITY** 100 mm²/s**OPERATING TEMPERATURE** -20 °C bis 120 °C**NLGI CLASS** 00**FIELD OF USE**

- transmission
- roller bearing
- bearings
- Linear guides & ball screws

BUSINESS

- Power Tools
- drive technology
- Wood

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

FUNCTIONALITY

- fluid grease

PACKING

- 250 g tube
 - 100 g cartridge
 - 380 g LubeShuttle
 - 400 g cartridge
 - 1 kg can
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com