



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KP2G-20

Special adhesive grease for bearings and gears GLL 6/N2

ELKALUB GLL 6/N2 is a special grease based on mineral oil. ELKALUB GLL 6/N2 is extremely long-fibred, adhesive and resistant to pressure and centrifugal forces for temperatures from -15 °C up to +100 °C. ELKALUB GLL 6/N2 is used for the lubrication of roller bearings and gears in the low speed range (speed factor ndm < 300.000), for open gear wheels in eccentrics as well as for slow turning slide bearings. ELKALUB GLL 6/N2 has antinoise qualities and is water-resistant.

BASE OIL mineral oil

THICKENER Lithium complex

VISCOSITY 272 mm²/s

OPERATING TEMPERATURE -15 °C bis 100 °C

NLGI CLASS 2

FIELD OF USE

- roller bearing
- bearings
- open gears
- racks

BUSINESS

- Power Tools

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- drive technology
- bearing manufacturer
- plant construction

FUNCTIONALITY

- lubricant

PACKING

- 250 g tube
 - 400 g cartridge
 - 5 kg bucket
 - 18 kg hobbock
 - 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com