



KP3G-15

## Special adhesive grease for bearings and gears GLL 6/N3

ELKALUB GLL 6/N3 is a special grease based on mineral oil. ELKALUB GLL 6/N3 is extremely long-fibred, adhesive and resistant to pressure and centrifugal forces for temperatures from -15 °C up to +100 °C. ELKALUB GLL 6/N3 is used for the lubrication of roller bearings and gears in the low speed range (speed factor ndm < 300.000), for open gear wheels in eccentrics as well as for slow turning slide bearings. ELKALUB GLL 6/N3 has antinoise qualities and is water-resistant. Examples for application: Open gear wheels, points of lubrication with centrifugal losses, poorly sealed bearings.

**BASE OIL** mineral oil**THICKENER** Lithium complex**VISCOSITY** 272 mm<sup>2</sup>/s**OPERATING TEMPERATURE** -15 °C bis 100 °C**NLGI CLASS** 3**FIELD OF USE**

- roller bearing
- bearings
- open gears
- racks

**BUSINESS**

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- Power Tools
- drive technology
- bearing manufacturer
- plant construction

---

#### FUNCTIONALITY

- lubricant

---

#### PACKING

- 250 g tube
  - 400 g cartridge
  - 5 kg bucket
  - 18 kg hobbock
  - 50 kg hobbock
  - 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)