



M2C5

Special assembly grease VP 881

The ELKALUB VP 881 grease was specially developed for connecting fittings in hydraulic lines. A uniform tightening torque is achieved with this grease. The screw connections can usually be loosened again without any problems.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

BASE OIL mineral oil

THICKENER Others

VISCOSITY 380 mm²/s

OPERATING TEMPERATURE 5 °C bis 40 °C

NLGI CLASS 2 - 3

BUSINESS

- Automotive
-

FUNCTIONALITY

- assembly grease
-

PACKING

- 5 kg bucket
- 18 kg hobbock

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- 50 kg hobbock
 - 150 kg barrel
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com