



Synthetic Oil Spray FLC 9010 H1 Halal



ELKALUB FLC 9010 is an oil spray, based on our long time approved synthetic oil LFC 9220 (ISO VG 220). The spray slips into narrow gaps and slits and offers paramount lubrication and moistening at all places to be greased. A unique anti-corrosion lub film guarantees best protection against wear. ELKALUB FLC 9010 is recommended to be used in temperature range from -35 °C till +160 °C. Ready for use with following applications: Gear chains, joints, hinges, guides, gripper shafts of printing machines, slide- and roller bearings. Remarks: In all practical working situations where contact with water, steam, acids and alkalis (pH-values 2 to 11 at 50 °C) cannot be excluded, it is better to choose our grease spray with H1 approval ELKALUB FLC 367.

BASE OIL Poly-alpha-olefin

OPERATING TEMPERATURE -35 °C bis 160 °C

VISCOSITY AT 40 ° C (ACTIVE SUBSTANCE) 220 mm²/s

FIELD OF USE

- bearings
- chain
- Guides & Curves
- bed ways

BUSINESS

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- print
- drive technology
- bearing manufacturer
- plant construction

FUNCTIONALITY

- Low-temperature grease
- Food grease
- corrosion protection
- universal

PACKING

- 400 ml of aerosol
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com