



# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**

KP2K-20

## Universal grease for bearings and gears GLL 7/N2

ELKALUB GLL 7/N2 is a lithium-saponified multipurpose grease, which is highly resistant to pressure, adhesive and resistant to oxidation. ELKALUB GLL 7/N2 has a special ELKALUB-additivation for the lubrication of roller and slide bearings (under medium up to heavy loads) for temperatures from -20 up to +120° C. ELKALUB GLL 7/N2 is particularly suited for points of lubrication with high centrifugal losses and where there is danger of the lubricant being washed out by water. The grease can be used up to a speed index (ndm\*) of about 400.000.

**BASE OIL** mineral oil

**THICKENER** Lithium complex

**VISCOSITY** 97 mm<sup>2</sup>/s

**OPERATING TEMPERATURE** -20 °C bis 120 °C

**NLGI CLASS** 2

**FIELD OF USE**

- roller bearing
- bearings

**BUSINESS**

- print
- drive technology
- bearing manufacturer
- plant construction

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

## FUNCTIONALITY

- adhesive grease
  - universal
- 

## PACKING

- 250 g tube
  - 400 g cartridge
  - 5 kg bucket
  - 18 kg hobbock
  - 50 kg hobbock
  - 150 kg barrel
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)