



Grease spray FLC 367 H1 Halal



ELKALUB FLC 367 is a partly synthetic EP-grease spray with high adhesive strength for the lubrication of chains, slideways, disk cams, gear racks etc. under an increased influence of water, vapour, acids and alkalis (in the pH-range 2-11 up to 50 °C). Even after cleaning procedures there remains a very thin lubricating film which at the same time protects against corrosion. ELKALUB FLC 367 penetrates well into joints and gaps. The product is suitable for application in the temperature range from -20 °C up to +130 °C (short time +180 °C). ELKALUB FLC 367 is NSF H1-approved and is therefore suited for environments with incidental food contact. Registration no. (H1): 126161

☐ ☐

☐☐☐ -20 °C bis 130 °C

40°C☐☐☐ (☐☐☐) 165 mm²/s

☐

- ☐☐☐
- ☐☐☐☐☐
- ☐☐☐
- ☐☐☐☐☐☐

☐

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

☐

- ☐
- ☐
- ☐
- ☐

☐

- 400☐

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com