



KPF2G-10

## Adhesive grease for the food industry GLS 388/N2 H1 Halal



ELKALUB GLS 388/N2 is an extremely adhesive aluminium complex soap grease based on partly synthetic base oils with a high resistance to water (also salt water). ELKALUB GLS 388/N2 is suitable for temperatures from -10 °C up to +100 °C. The main areas of application are slow-turning drive elements such as joints, shafts, open cogwheels, sliding motions in the food industry. ELKALUB GLS 388/N2 is most suitable for pairings of nonferrous metals and steel.

□□ □□ □α□□ □□

□□□ □□□□ □□□□□ □□

□□ 72 mm<sup>2</sup>/s

□□□□ -10 °C bis 100 °C

NLGI □ 2

□□

- □□□□□□
- □□□□
- □□□□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

- □□
- □□
- □□□□
- □□□□

---

□□

- □□
- □□□□□□□□

---

□□

- 250□□
- 400□□□
- 5□□□
- 18□□□□□
- 50□□□□□
- 150□□□

---

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)