



# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**

KPFHC1N-40

## High speed grease GLS 961/N1

**ELKALUB GLS 961/N1** is a polyurea thickened high speed grease.

The combination of a fully synthetic base oil (polyalphaolefin) with low base oil viscosity and a stable polyurea thickener allows speed values of > 2 million [mm/min].

A typical area of application for **ELKALUB GLS 961/N1** are therefore miniature ball bearings and gears as well as spindle bearings in CNC machines.

The synthetic oil base, the low base oil viscosity and the soft consistency allow **ELKALUB GLS 961/N1** to be used even at temperatures well below freezing. At high temperatures, the high-quality base oil guarantees very good resistance to oxidation and aging.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

□□ □α□□

□□□ □□

□□ 48 mm<sup>2</sup>/s

□□□□ -40 °C bis 160 °C

NLGI □ 1

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)

- 10000

100

- 100000
- 100000

100

- 100
- 10000

100

- 400000
- 50000
- 1800000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)