



ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

KPFHC2N-20

high-load grease VP 873 H1 Halal



ELKALUB VP 873 is a grease for heavily loaded roller bearings (especially tapered and spherical roller bearings, cam rollers).

Due to the high load-bearing capacity and the high wear protection, **ELKALUB VP 873** is also used as a lubricant in open gears. The lubrication points benefit from the adhesive formulation, which is also responsible for a high level of corrosion protection and water resistance.

The addition of solid lubricants supports sliding pairings and ensures emergency running properties.

ELKALUB VP 873 is suitable for metal-plastic combinations. Due to the diversity of plastic materials, a previous resistance test is recommended.

A special application of **ELKALUB VP 873** is as an assembly paste for stainless steel screw connections in the food industry. The grease prevents cold welding.

□□ □□ □□

□□□ □□ □□□□□

□□ 460 mm²/s

□□□□ -20 °C bis 140 °C

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

NLGI 1 - 2

00

- 0000
- 0000
- 000000
- 0000
- 0000000

00

- 00
- 00
- 00000
- 0000
- 00000

00

- 00
- 00
- 00
- 00000
- 00000000

00

- 25000
- 400000
- 1000
- 5000
- 1800000
- 5000000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com