



## High-temperature grease spray FLC 95

ELKALUB FLC 95 is an entirely synthetic, creepable grease spray with excellent adhesion and EP properties. It is free from silicones. ELKALUB FLC 95 is used for longer intervals of relubrication for temperatures up to 150 °C. However, it can also be used up to 220 °C if there is frequent relubrication. Examples of use for ELKALUB FLC 95 are chains (e.g. shrink tunnels, drying tunnels), joints and spindles in the high temperature and hot air range. The spray is bottled free from FCKW.

□□ □α□□

□□□ □□

□□□□ -30 °C bis 170 °C

40°C□□□□ (□□□□) 400 mm<sup>2</sup>/s

□□

- □□□□
- □□
- □□□□□□
- □□□□
- □□□□□□

□□

- □□□□
- □□
- □□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□□□
- 

□□

- □□
  - □□□
  - □□□□□□□□
  - □□□□
- 

□□

- 400□□□□□□
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com