



## High-temperature oil spray FLC 4010 P H1 Halal



FLC 4010 P is used for the lubrication of chains, joints, rollers, guides, spindles in the temperature range from -35 °C till +180 °C (with continuous relubrication up to +200 °C). The high creep ability ensures that internal friction surfaces prone to wear are lubricated. After the solvent has evaporated, a transparent, very pressure and adhesive film remains. In offset printing machines, ELKALUB FLC 4010 P is suitable for the lubrication of gripper seats (especially under UV light conditions and in the coating area). ELKALUB FLC 4010 P is supplied in 300 ml pump spray cans.

□□ □

□□□ □□

□□□□ -35 °C bis 180 °C

40°C □□□□ (□□□□) 160 mm<sup>2</sup>/s

□□

- □□□□
- □□□□□□

□□

- □□
- □□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
- □□□□□
- □□□□
- □□
- □□□□

□□

- □□
- □□
- □□
- □□□□□□□□

□□

- 300□□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com