



KPHC2P-40

## High-temperature grease GLS 966/N2

□□ □□□□

□□□ □□ □□□□□

□□ 150 mm<sup>2</sup>/s

□□□□ -40 °C bis 160 °C

NLGI □ 2

□□

- □□□□
- □□□□
- □□□□

□□

- □□□□
- □□
- □□□□□

□□

- □□
- □□

□□

- 250□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

# ELKALUB



**Hochleistungs-Schmierstoffe**  
**High Performance Lubricants**

- 400□□□
  - 1□□□
  - 5□□□
  - 18□□□□
  - 50□□□□
  - 150□□□
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)