



Chain and adhesive lubricant FLC 8 H1 H1 Halal



ELKALUB FLC 8 H1 is our chain lubricant ELKALUB FLC 8 H1 in spray form. ELKALUB FLC 8 H1 is a further development of our chain lubricant ELKALUB LA 8. The lubricating film has a good spreading capability and protects against corrosion. It has excellent boundary lubrication properties and is very adhesive and resistant to centrifugation up to 80 °C. ELKALUB FLC 8 H1 is recommended for use in heavy drive chains, cams, disk cams, open cogwheels, slideways and spindles.

□□ □□

□□□ □□

□□□□ -20 °C bis 120 °C

40°C□□□□ (□□□□) 6000 mm²/s

□□

- □□
- □□□□□□
- □□□□
- □□□□□□□□
- □□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

□□

- □□
- □□
- □□
- □□□□
- □□□□
- □□
- □□
- □□□□

□□

- □□
- □□□
- □□□□□□□□
- □□□□

□□

- 400□□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com