



## Chain and sliding spray FLC 1010/1012

ELKALUB FLC 1010/1012 is an oil spray with no solid additive which is based on our extremely heavy-duty ELKALUB LA 1 concentrated lubricant. It is resistant to ageing, chemically neutral, removes dirt, protects against corrosion, does not gum and undercuts moisture. When the part which is to be lubricated is sprayed, there is only a very thin, transparent and adhesive film remaining. The extremely penetrable special lubricant offers a guarantee of forming a lubricating film even in tight spaces and lubricating reliably. It restores movement to slightly rusty or heavily carbonised parts and supports the removal of this. Although ELKALUB FLC 1010/1012 penetrates tight spaces very well, it does not spread across surface areas very well. This is advantageous for grippers and transport chains, for example. ELKALUB FLC 1010/1012 is supplied as an aerosol spray (400 ml). The product is also available as a pump spray can (FLC 1010/1012 P) or as a liquid container (FLC 1010/1012 liquid).

☐ ☐ ☐☐

☐☐☐ -20 °C bis 120 °C

40°C☐☐☐ (☐☐☐) 60 mm<sup>2</sup>/s

☐☐

- ☐☐☐☐
- ☐☐
- ☐☐☐☐☐☐☐

☐☐

- ☐☐
- ☐☐☐☐
- ☐☐

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

- □□
  - □□□□
- 

□□

- □□□□
  - □□
- 

□□

- 5□□
  - 400□□□□□
- 

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | [info@elkalub.com](mailto:info@elkalub.com) | [www.elkalub.com](http://www.elkalub.com)