



Chain and adhesive lubricant LA 8 H1 H1 Halal



ELKALUB LA 8 H1 is a product based upon our well-known ELKALUB LA 8. However, ELKALUB LA 8 H1 offers an increased protection against wear and considers the regulations for the use in the food industry. It is adhesive, resistant against centrifugal losses, penetrates well into gaps and offers a good protection against corrosion. The viscosity of ELKALUB LA 8 H1 has been lowered a bit as compared with ELKALUB LA 8. By that, we take into account the increasing use of paper powder in printing presses. In spite of this, the spin-off behaviour of ELKALUB LA 8 H1 is better in the higher temperature range. As compared with ELKALUB LA 8, we managed to extend the operation temperature range. Examples for application: Disk cams, delivery chains, open gear wheels, eccentrics and guide rails.

□□ □ □□

□□□□ -10 °C bis 80 °C

40°C □□□□ 2300 mm²/s

□□

- □□□□
- □□
- □□□□□□
- □□□□
- □□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

□□

- □□
- □□
- □□
- □□□□
- □□□□
- □□□□

□□

- □□
- □□□□□□□□

□□

- 1□□
- 2.5□□□
- 5□□□
- 200□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com