



Chain and adhesive lubricant LA 8 P

ELKALUB LA 8P is a product based on our special lubricant ELKALUB LA 8. Although it appears to be very solid at rest, it has a very good penetration ability under motion and is well conveyable in central lubrication units. Compared with ELKALUB LA 8, we were able to rise the upper temperature limits considerably and ameliorate the behaviour of centrifugation. This is of advantage for delivery chains in highly charged printing presses under the influence of higher temperatures. Applications: Cam plates, delivery chains, open cogwheels, eccentrics and guide rails.

□□ □ □□

□□□□ -10 °C bis 80 °C

40°C □□□□ 1700 mm²/s

□□

- □□□□
- □□
- □□□□□□
- □□□□
- □□□□□□

□□

- □□
- □□□□
- □□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com



- □□□□□□□□
-

□□

- 2.5□□□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com