



KPFK2U-40

PFPE high-temperature grease GLS 595/N2 H1 Halal



ELKALUB GLS 595/N2 is a high temperature grease mainly used for the lubrication of roller and slide bearings in the temperature range from -40 °C up to +250 °C. ELKALUB GLS 595/N2 is resistant to acids and alkalis as well as to organic solvents. Please note: ELKALUB GLS 595/N2 may not be mixed with other lubricants. Due to its high chemical stability ELKALUB GLS 595/N2 has been used for many years as nozzle sealing compound for adhesive machines at the end of the work process. Most important: Before applying the lubricant the surfaces have to be thoroughly cleaned as the lubricant will adhere only to surfaces free of oil, grease and dirt. Recommendation: for cleaning use ELKALUB LFC 500.

□□ □□□□

□□□ □□□□□

□□ 360 mm²/s

□□□□ -40 °C bis 250 °C

NLGI □ 2

□□

- □□□□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

- 0-1000
- 100

100

- 100
- 100
- 100
- 10000
- 10000
- 10000

100

- 100
- 100
- 100

100

- 25000
- 40000
- 1000
- 5000
- 180000
- 500000
- 150000

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com