



PTFE spray FLC 9025 H1 Halal



ELKALUB FLC 9025 H1 PTFE spray is an Synthetic oil spray with PTFE. Excellent sliding lubrication properties, highest wear protection and emergency running properties thanks to solid lubricants. For guides, joints, shafts and bushings and other sliding elements. With H1 registration for use in the food and pharmaceutical industries.

□□ □α□□

□□□□ -40 °C bis 160 °C

40°C□□□□ (□□□□) 58 mm²/s

□□

- □□□□
- □□□□□□□□
- □□

□□

- □□
- □□□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

Produkt-Beratung: +49 7454 9652 0 | Mo–Fr 09–16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
- □□□/□□□
- □□□□
- □□

□□

- 400□□□□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com