



Rust remover spray FLC 1040

ELKALUB FLC 1040 is a consistently acting rust remover with additional lubrication effect. For strong corrosion we recommend a repetitive application in intervals. ELKALUB FLC 1040 is recommended for temperatures between -20 °C to +120 °C. Remark: For larger assembly components or threads it has been proved to use the extremely penetrable Chain Spray ELKALUB FLC 1010 after the evaporation or the rust remover ELKALUB FLC 1040. ELKALUB FLC 1040 can be delivered in aerosol cans or as liquid.

□□□□ -20 °C bis 120 °C

□□

- □□
- □□
- □□□□
- □□□□
- □□
- □□
- □□□□□
- □□□□

□□

- □□
- □□/□□□□□
- □□□□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

- 5□□□
 - 400□□□□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com