



## Bearer ring oil VP 785

ELKALUB VP 785 has been specially developed for the lubrication of cylinder bearings in printing presses. The product offers a high protection against corrosion, does not lead to and has varnish dissolving properties. Furthermore, ELKALUB VP 785 can be used as universal EP-concentrate for the lubrication of highly charged machinery elements. In order to make best use of the product's EP-properties, we recommend to apply the ELKALUB VP 785 in the temperature range from approx. +20 °C up to +80 °C.

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

□□ □□□

□□□□ -20 °C bis 120 °C

40°C□□□□ 43 mm<sup>2</sup>/s

□□

- □□□

□□

- □□

□□

- 1□□
- 5□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

**Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH  
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com