



KPSi2R-40

silicone grease GLS 794/N2 H1 Halal



ELKALUB GLS 794/N2 is a fully synthetic special grease for application in the food and beverage industry (sliding procedures, e.g. taps, valves, fittings). ELKALUB GLS 794/N2 does not have any influence on the formation of the beer foam (see report from Weihenstephan). The product is very resistant against water and steam and can be used for operating temperatures from -40 °C up to +180 °C. ELKALUB GLS 794/N2 is compatible with seals made of Viton, EPDM and NBR.

□□ □□

□□□ □□□□□

□□ 750 mm²/s

□□□□ -40 °C bis 180 °C

NLGI □ 2

□□

- □□□□O-□□□□□
- □□

□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

- □□
- □□
- □□□□

□□

- □□
- □□
- □□
- □□

□□

- 50□□□□
- 200□□□□
- 250□□
- 380□LubeShuttle
- 400□□□
- 5□□□
- 18□□□□
- 50□□□□
- 150□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com