



Silicone special grease GLS 42

ELKALUB GLS 42 is a smooth special silicone grease for all types of sliding processes.

Due to the solvent content, the grease can be sprayed easily. After the subsequent evaporation of the solvent, a highly adhesive and highly viscous lubricating film remains.

If required, the solvent content can be varied and adapted to the specific spray application.

ELKALUB GLS 42 can be used in a wide temperature range (-30 °C /+180 °C); for use at higher temperatures, wait for the solvent to evaporate (typically: 12-36 hours/room temperature).

This is a special product which can be produced individually for you on request. Smaller quantities can apply. Please just talk to us.

□□ □□

□□□ □□□□□

□□ 370 mm²/s

□□□□ -30 °C bis 180 °C

NLGI □ 1

□□

- □□□□
- □□□□O-□□□□□
- □□
- □□□□□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

□□

- □□
- □□□□
- □□

□□

- □□
- □□□/□□□

□□

- 1□□□
- 5□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com