



Silicone Spray FLC 700

Highly viscous glidant (approx. 22500 mm²/s at 40°C) which at the same time conserves the surface and protects against corrosion. After evaporation there remains a non-sticky film of long endurance. The transparent lubricating film is dirt repelling and does not leave any spots. Application for paper, cardboard, wood, rubber, plastics and fibre materials. Spray filling with: light hydrocarbons, butane.

□□ □□

□□□□ -50 °C bis 170 °C

40°C □□□□ (□□□□) 22500 mm²/s

□□

- □□□□-□□□□□
- □□□□□□□

□□

- □□
- □□□□
- □□
- □□□□□
- □□□□

□□

- □□□/□□□
- □□□□

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.

 **Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr**

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH
Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com

ELKALUB



Hochleistungs-Schmierstoffe
High Performance Lubricants

□□

- 5□□
 - 400□□□□□
-

These data are released in good faith and express our knowledge as of today. We reserve the right to modify and/or supplement them.



Produkt-Beratung: +49 7454 9652 0 | Mo – Fr 09 – 16 Uhr

ELKALUB Hochleistungs-Schmierstoffe | Chemie-Technik GmbH

Robert-Bosch-Straße 19 | DE-72189 Vöhringen | Tel.: +49 7454 9652-0 | Fax: +49 7454 9652-35 | info@elkalub.com | www.elkalub.com